

-----Section 1. Identification

Product Name: ROYALSIL HI-PURITY AMEO

Product Use: Treat mineral fillers, adhesion promoter in various paints, adhesives, caulks and

sealants. Certain plastics.

Effective Date: 18 May 2020 Replaces: 21 May 2019

Supplier Information: ROYALSIL, Inc. 25 Lancelot Lane

Mount Laurel, NJ 08054-1912

USA Emergency Phone Number:

CHEMTREC (24-hr/7 days): 1-800-424-9300 Refer to ROYALSIL, Inc. contract # CCN674872.

Section 2. Hazard(s) Identification

Emergency Overview: Clear combustible liquid. Prolonged contact causes skin burns and eye damage. Ingestion or inhalation will be harmful. Harmful to aquatic life with long lasting effects.

GHS Classification:

Skin CorrosionCategory 1BSerious Eye DamageCategory 1Acute toxicity (Oral)Category 4







GHS Pictograms:

GHS Label: DANGER

POTENTIAL HEALTH EFFECTS: CODE OF HAZARD STATEMENTS:

Physical Hazards

H227- Combustible liquid.

Health Hazards

H227- Combustible liquid.

H302- Harmful if swallowed.

H314- Causes severe skin burns and eye damage.

H332- Harmful if swallowed.

Environmental Hazards

H412- Harmful to aquatic life with long lasting effects.



CODE OF PRECAUTIONARY STATEMENTS:

General

P101- Keep out of reach of children.

P103- Read label before use.

Prevention Statements

P202- Do not handle until all safety precautions have been read and understood.

P210- Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233- Keep container tightly closed.

P261- Avoid breathing dust/fume/gas/mist/vapor/spray.

P262- Do not get in eyes, on skin or on clothing.

P264- Wash thoroughly after handling using this product.

P270- Do not eat, drink, or smoke when using this product.

P271- Use only outdoors or in a well-ventilated area.

P273- Avoid release to the environment.

P280- Wear protective gloves/protective clothing/eye protection/face protection.

Response Statements

P301- P330- P331- IF SWALLOWED: Rinse mouth. Do Not induce vomiting.

P303- P353- P361- IF ON SKIN (or hair): take off immediately all contaminated clothing. Rinse skin with water/shower.

P304- P340- IF INHALED. Remove victim to fresh air and keep at rest in apposition comfortable and breathing.

P305- P338- P351- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310- Immediately call a Poison Center or doctor/physician.

P363- Wash contaminated clothing before reuse.

P370- P378- In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

Storage

P403 - P235- Keep cool. Store in well-ventilated place.

P405- Store locked up.

Disposal

P501- Dispose of contents/container to an approved waste disposal plant.

ROUTES OF ENTRY: Eye contact, skin adsorption, ingestion and inhalation.

CARCINOGENICITY: None listed in IARC, OSHA or NTP.

Section 3. Composition/Information on Ingredients

Ingredients	CAS No.	EINECS No.	%	Reach No.
3-Aminopropyltriethoxysilane	919-30-2	213-048-4	<u>></u>	No
Ethanol	64-17-5	200-578-6	<u>≤</u> 1	Yes



Section 4. First Aid Measures

General Advice: In the case of accident or if you feel unwell, seek medical advice immediately. When symptoms persist or in all cases of doubt seek medical advice.

Eye Contact: Flush eyes with water immediately while holding eyelids open. Remove contacts, if worn, after initial flushing and continue flushing for at least 15 minutes. Seek medical attention if irritation persists.

Skin Contact: Use soap and water to remove from the skin, remove contaminated clothing, clean thoroughly before reuse. If irritation persists, contact a physician.

Inhalation: Move to fresh air. If not breathing, give rescue breathing. If breathing is difficult, give oxygen. Seek medical attention if breathing is still difficult.

Ingestion: If swallowed, get medical attention immediately. DO NOT INDUCE VOMITING.

Never give anything by mouth to an unconscious person.

Note to Physician: Treat symptomatically and supportively.

Section 5. Fire Fighting Measures

Flash Point: 204.8°F (96°C) Combustible liquid **Flammability Limits**: LEL: 0.8% UEL: 4.5%

Fire Fighting Media: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. **Special Fire Fighting Procedures:** In case of fire cool endangered containers with water. Hazardous fumes in fires, specific to the product are ammonia, alcohols, amines, nitrogen and silicon oxides. First responders need to wear full-bunker gear with Self Contained Breathing Apparatus (SCBA), never enter a confined space unless fully protected with proper personal protective equipment (PPE).

Section 6. Accidental Release Measures

Use personal protective equipment, see section 8.

Clean-up Procedures: Stop the source of the release if you are not put at risk. Use inert absorbent material (such as earth, diatomaceous earth, vermiculite) to absorb the spill, use non-sparking shovel to pick up absorbent for disposal. Assure sufficient ventilation.

Spills and Leaks: Dispose in accordance to local, state or Federal regulations.

Section 7. Handling and Storage

Handling: Provide good ventilation. Wear personal protective equipment, see section 8. Do not get into eyes, on skin and on clothing. Do not breathe vapors or mists. Use with adequate ventilation. Wash thoroughly after handling.

Storage: Store in original labeled container. Keep in cool and dry areas.

Section 8. Exposure Controls/Personal Protection



Introductory Remarks: Use a local exhaust ventilation or other engineering controls to minimize airborne exposure. A safety shower and eye wash should be readily available. Ethanol permissible exposure limit (PEL) is 1 ppm.

Personal Protection:

Eyes: Wear safety goggles or face shield to prevent eye contact.

Body: Chemical apron, long sleeve shirts, long pants, socks, and rubber boots.

Hands: Chemical resistant gloves.

Respiratory: Wear an approved respirator that provides protection from this product if the

airborne concentrations exceed the recommended exposure limits.

Section 9. Physical and Chemical Properties

Physical State,	Clear liquid with	Vapor Pressure	< 13 hPa @ 212°F
Color, Odor	amine odor		(100°C)
Ignition	518°F (270°C)	Density(water=1)	> 0.946 @ 77°F
Temperature			(25°C)
pН	11 @ 20g/L @ 68°F	Solubility	Reacts with water
	(20°C)	·	
Freezing Point	-94°F (-70°C)	Boiling Point	251.6°F (122°C)
Flash Point	204.8°F (96°C)	Vapor Density	7.64
		(Air)=1.0	

Section 10. Stability and Reactivity

Chemical Stability: Considered stable under normal ambient temperatures.

Hazardous Decomposition: In complete combustion, oxides of carbon, nitrogen and silicate are

formed.

Hazardous Polymerization: Will not occur.

Incompatibility- Materials to Avoid: Acids and strong oxidizing agents.

Section 11. Toxicological Information

Toxicology: Acute Oral LD₅₀ (rat) = 1,780 mg/kg

Acute Dermal LD_{50 (rat)} = 3,800 mg/kg Acute Inhalation LC_{50 (rat)} = 5 ppm (6 hour)

Skin Irritation: Causes burns in rabbits. **Eye Irritation**: Causes eye damage. **Acute Eve Irritation**: Severe.

Acute Skin Irritation: May cause burns.

Acute Dermal Toxicity: Not expected to be toxic through the skin.

Acute Inhalation Toxicity: Expected to be an irritant to the respiratory system.

Reproductive Toxicity: No evidence of adverse effects on sexual function and fertility or on

development, based on animal experiments.



Carcinogenic Effects: None listed in IARC, OSHA or NTP.

Section 12. Ecological Information

Ecotoxicity: $LC_{50(Zebra\ Fish)} = 934mg/L\ 96\ hour$

 $LC_{50(Water\ Flea)} = 331\ mg/L$ $EC_{50(Green\ Algae)} => 1,000\ mg/L$

This is to aquatic organisms.

Environmental Fate: This product not readily bio-degradable. There is low bio accumulative potential. Very low adsorption in soil.

Section 13. Disposal Considerations

Waste Disposal Method: Whatever cannot be saved for recovery or recycling should be managed by the local, state or Federal Regulations.

Container Handling and Disposal: All containers should be triple rinsed and disposed of according to local, state and Federal regulations.

Section 14. Transport Information

Shipping Name: ROYALSIL HI-PURITY AMEO

Proper Shipping Description (Ground):

UN3267, Corrosive, Liquid, Basic, Organic, N.O.S., (3-Aminopropyltriethoxysilane), 8, II,

IATA: (Cargo aircraft only)

UN3267, Corrosive, Liquid, Basic, Organic, N.O.S., (3-Aminopropyltriethoxysilane), 8, II, Use packing instruction 812. The maximum net capacity is 7.93 gal (30 L).

IMO (Water):

UN3267, Corrosive, Liquid, Basic, Organic, N.O.S., (3-Aminopropyltriethoxysilane), 8, II, Use packing instruction P001.



Section 15. Regulatory Information

EPCRA 311/312 Categories: Immediate (Acute) Health Effects: Yes

Delayed (Chronic) Health Effects: Yes Fire Hazard: Yes Sudden Release of Pressure No Reactivity: Yes

Right to Know Classification: Ethanol is listed in the states of CA MA, NJ and PA. 3-Aminopropyltriethoxysilane is listed in MA, NJ and PA

TSCA: Both ingredients are listed.

Reportable Quantity (RQ): Ethanol 5,000 lbs. (2,270 KGS.) Not reached in current packaging.

Prop. 65: None

CANADA: These two products are listed in either DSL or NDSL.

Compounds are listed as chemical inventories of Australia, Canada, China, European Union, Germany, Japanese, Korea, Ministry of International Trade and Industry, Netherlands, Philippines, Switzerland, Taiwan, United Kingdom and United States of America.

Abbreviations:

CAS#	Chemical Abstract Service Number					
$^{\circ}\mathrm{C}$	Celsius Temperature Scale	°F	Fahrenheit Temperature Scale			
EINECS #	EINECS # European Inventory of Existing Chemical Substances Number					
hPa	Hectopascal	LD_{50}	Lethal Dose Oral or Dermal			
LC_{50}	Lethal Inhalation	LEL	Lower Explosive Limit			
UEL	Upper Explosive Limit	PEL	Permissible Exposure Limit			
PPE	Personal Protective Equipment	Prop.	Proprietary			
PSI	Pounds Per Square Inch	NA	Not applicable			
ND	Not Determined	STEL	Short Term Exposure Limit			
TLV	Threshold Limit Value	TSCA	Toxic Substance Control Act			
TWA	Time Weighted Average					



Hazardous Material

ROYALSIL HI-PURITY AMEO

National Fire Protection

Section 16. Other Information

Information System		Association		
HMIS		NFPA		
2	Health	2	Health	
1	Fire	1	Fire	
2	Reactivity	2	Instability	
Н	Personal Protection		NA	

Health 4 Deadly 3 Extreme Danger 1 Slight hazard 0 No hazard 2 Dangerous $4 < 73 \, {}^{\circ}\text{C}$ $1 > 200 \, {}^{\circ}\text{C}$ 0 Will not burn Fire 3 < 100 °C $2 < 200 \, ^{\circ}\text{C}$ Reactivity/ 4 – May detonate 3 Explosive 2 Unstable 1 Normally stable 0 Stable Instability

Prepared by: Dennis E. Belau Reviewed by: Rosario A. Licciardello ROSARIO@ROYALSIL.com

This Safety Data Sheet (SDS) meets the requirements of the Federal OSHA Hazard Communication Standard (29 CFR 1910.1200) this product has been classified according to the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all information required by CPR.

This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability or completeness.

It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own use. We do not accept liability for any loss or damage that may occur from the use of this information.

Nothing herein shall be construed as a recommendation for uses which infringe on valid patents or as extending the license under valid patents. This SDS provides selected regulatory information on this product, including its components.

This is not intended to include all regulations. It is the responsibility of the user to know and comply with all applicable rules, regulations and laws related to the product being used.



DISCLAIMER

Strictly for Commercial or Research and Development use only. Not intended for drug, household or other noncommercial uses.

The use of "Qualitative Determinations of Organosilanes" is subject to many variables which can be environmentally or human caused which may allow the reading of results to be inaccurate.

The user of this information takes full responsibility in how these tests are performed and the seller in no way expressed, written or implied is responsible for the interpretation of the results. All use of these tests is the full responsibility of the user.

WARRANTY

The information above in the Safety Data Sheet is believed to be accurate and represents the best information currently available to ROYALSIL Inc and its supplier.

However, we make no warranty of merchantability or any other warranty, expressed or implied, with respect to such information, and we assume no liability resulting from its use.

Users should make their own investigations to determine the suitability of the information for their purposes. In no event shall ROYALSIL Inc. or its supplier be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, how so ever arising, even if ROYALSIL Inc and its supplier has been advised of the possibility of such damages. (REV: 9-4-16)